

MARC NEWSON BATH/SHOWER, MODEL 5450.6XX

- Contemporary styling
- Cast brass valve body
- Washerless ceramic disc valve cartridge cycles from "Off" to "Hot" to "Cold"
- Pressure balance cartridge maintains constant output temperature in response to changes in relative hot and cold supply pressures
- Integral diverter provides positive shutoff allowing for use with 2 applications. (For example, showerhead and handspray or showerhead and tub spout)
- One valve body with optional diverter plug allows for quick conversion from Bath/Shower to Shower Only
- Hot and cold can be reversed quickly and easily for back-to-back installations
- Wide roughin range from 1-5/8" to 3-1/4"
- Adjustable hot limit safety stop included
- 1/2" NPT inlets and outlets
- Includes escutcheon plate and plaster guard (which can serve as a thin wall support)
- Available in Chrome only

5450.601 Shower Only

5450.602 Bath/Shower

Extension Kits

- M962818-XXX0A** PB Bath/Shower Extension Kit
- M961818-XXX0A** PB Shower Extension Kit




Showerhead Maximum Flow Rate: 2.5 gpm (9.5L/min.)

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASME A112.18.1
CSA B125
ASSE 1016



ROUGH-IN DIAGRAM
SHOWN ON
REVERSE SIDE

