

REPRISE BATH/SHOWER WITH BUILT-IN DIVERTER, MODEL 5535.XXX

- Traditional styling
- Cast brass valve body
- Washerless ceramic disc valve cartridge cycles from "Off" to "Hot" to "Cold"
- Pressure balance cartridge maintains constant output temperature in response to changes in relative hot and cold supply pressures
- Integral diverter provides positive shut off allowing for use with 2 applications. (For example, showerhead and handspray or showerhead and tub spout)
- One valve body with optional diverter plug allows for quick conversion from Bath/Shower to Shower Only
- Hot and Cold can be reversed quickly and easily for back-to-back installations
- Wide roughin range from 1-5/8" to 3-1/4"
- Adjustable hot limit safety stop
- 1/2" NPT inlets and outlets
- Includes escutcheon plate and plaster guard (which can serve as a thin wall support)

Specify assembly finish: chrome, polished nickel, polished brass, or brushed nickel

5535.602 Bath/Shower

5535.601 Shower Only

Extension Kits

M962818-XXX0A PB Bath/Shower Extension Kit

M961818-XXX0A PB Shower Extension Kit




Showerhead Maximum Flow Rate: 2.5gpm (9.5L)

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASME A112.18.1
CSA B125
ASSE 1016



ROUGHIN DIAGRAM
SHOWN ON
REVERSE SIDE

